

The Professor - 27" Hot Roll Laminator

- Mount and laminate in one step
- Variable speed
- Digital display
- Easy threading



The **Professor** has been engineered to provide years of service with minimal maintenance. It laminates film up to 10 mils thick and mounts materials up to 3/16" thick. Its unique self-threading feature reduces the anxiety often associated with threading a laminator. The hot roll design permits simultaneous mounting and laminating using mounting boards with attached overlaminates.

Easy To Use

- Mounts and laminates in one step
- Simple controls
- LCD temperature display
- Variable speed
- Easy threading
- Preset roller pressure

Reliable

- More than 15 years of proven reliability
- Popular in schools, libraries, small graphics shops
- Made in the USA

Great Value

- Mount and laminate on one machine
- 2-year manufacturer's parts and labor warranty
- Toll free telephone support



PROFESSOR

PROFESSOR

The Professor - 27" Hot Roll Laminator

FEATURES

- **Variable speed** up to 10 feet per minute with thin films; thicker films apply better at lower speeds.
- **LCD temperature display** indicator light automatically turns off when desired temperature is reached.
- **Simple controls** icons and international symbols guide and alert operators to control and warnings.
- **Easy threading** automatically threads bottom idler after the operator has threaded the upper and lower film webs and closed the feed tray into its operating position.
- **Forced air cooling** allows laminating with thicker films. Without a film cooling system, thicker films would warp and ripple because they are still in the process of setting up when they exit the laminator.
- **Pre-set, spring loaded rubber rollers** assure correct and even laminating pressure.
- **Supply roll tension controls** allows easy adjustment by simply loosening or tightening control knobs on supply roll mandrels.
- **Reverse switch** helps avoid problems and clear misfeeds.
- **Attached safety shield** fixed to the machine and placed so the operator will put it in the guard position before laminating. The clear shield allows users to see their work with the safety shield in its proper protective position.
- **Removable power cord**
- **Made in the USA**
- **2-year manufacturer's parts and labor warranty**
- **Toll free telephone support**

OPTIONS

Stand

SPECIFICATIONS

Laminating width	up to 27"
Speed	0 – 10 feet per minute
Laminating roller diameter	2.25"
Laminating film roll core	1"
Maximum film gauge (thickness)	10 mil
Maximum laminating thickness	3/16"
Dimensions	35L x 14H x 16W
Shipping dimensions	39L x 16H x 18W
Weight / shipping weight	93 lbs / 102 lbs
Electrical	110v (220v optional) 15 amps

Specifications subject to change without notice.



PROFESSOR

PROFESSOR