

XL44 Pouch/Mounting Laminator

- Mounts and laminates in one step
- Simple operation
- Laminates up to 1-1/2 inches thick
- 2-year parts and labor warranty



The **LEDSCO XL 44** provides easy, cost effective, one-step mounting and laminating for customers who need larger format lamination. Great for mounting posters and prints.

Easy To Use

- Simple controls
- No real set up or threading needed

Great Value

- Laminating protects signs, prints, and other documents, eliminating replacement
- Versatile – laminate, mount, or mount and laminate in one step
- Pre-cut boards and mounting materials eliminate waste

Reliable

- 2-year manufacturer's parts and labor warranty
- Operator manual, training video, and toll free telephone support
- Made in the USA

FEATURES

- **Simple operation**- virtually no training needed.
- **Change laminate finishes** without rethreading and time consuming set up.
- **Easy access controls.**
- **Sleek, low profile design** for stand or tabletop use.
- **Our color coded consumables** allow even the newest operator to easily calculate job profitability and choose the proper materials to avoid costly errors.
- **Preset pressure and lamination speed.**
- **Adjustable position lamination rollers** allow laminating most substrates up to 1-1/2" thick.
- **Enclosed rollers** protect against accidental damage and contribute to operator safety.
- **Variable temperature control** allows laminating with a wide variety of materials.
- **Non-magnetic feed tray.**
- **Attached safety shield.**
- **Emergency stop.**
- **Removable power cord.**



XL44

XL44

XL44 Pouch/Mounting Laminator

OPTIONS



Stand

SPECIFICATIONS

Laminating width	up to 44 inches
Dimensions	62L x 16H x 19W
Shipping dimensions	66L x 24H x 20W
Weight/shipping weight	130 lbs / 200 lbs
Speed	1 fpm (foot per minute)
Electrical – 110 version	110-125v 15 amps 1250w 50/60 Hz
Electrical – 220 version	208-240v 10 amps 1500w 50/60 Hz
Laminating roll diameter	3-1/8 inches
Recommended film gauge (thickness)	up to 10 mil
Maximum laminating and cutting thickness	1-1/2 inch

- **Made in the USA**
- **2-year manufacturer's parts and labor warranty**
- **Toll free telephone support**
- **CE, NRTL, ETL certified for use in North America and Europe (220 version)**

Specifications subject to change without notice.



XL44

XL44