



FOLIANTEU, s.r.o.  
Stefanikova 1347/III  
293 01 Mlada Boleslav  
Czech Republic  
tel +420 326 370 711  
[foliant@foliant.eu](mailto:foliant@foliant.eu) | [www.foliant.eu](http://www.foliant.eu)

# FOLIANT GEMINI C 400

The FOLIANT Gemini C 400 is a manual high pressure laminating machine developed for a **digital printing machines outputs lamination**. The machine is equipped with a pneumatic system of laminating rollers pressure with an easy thrust control. A small compressor is integrated inside the machine frame. The machine has been designed with an operating width of 380 mm and it represents an ideal choice for professional single side lamination in digital shops and all other printing shops, printing and processing sheets up to B3+ size (the length of laminated sheets is not limited, in practice lamination it is ~70 cm). **Maximum speed is up to 15 meters/min.**



The machine's main feature is the pneumatic pressure system in a heavy duty mechanism enabling to achieve a very high working pressure, one single phase 220 – 240 V supply cable, a small integrated compressor inside the machine frame (i.e. no external source of pressured air is required), a nice design and an easy machine operation.

The machine is being supplied with a modular stand covered with a nicely designed side panels as a standard accessory. The machine requires a minimum floor space of 74 x 117 cm.

## LAMINATOR

The FOLIANT Gemini C 400 laminator maximum sheet size is 38 x 66 cm. The minimum sheet size is 30 x 25 cm (A4). The roll of a film is mounted on an easy handle shaft with a film tension control breaker. The shaft capacity is up to 3000 m of 24 - 31 microns film. The film holder unit is equipped with a trim splitter and a perforating wheel.

The laminating process is done between two laminating rollers - a highly polished chrome roller, and a lower hard rubber pressure roller. The laminating roller is heated with an infra-red heating spiral, with a sensitive contact temperature sensor. The pressure is pneumatically adjustable to achieve an extra high pressure between the laminating rollers. A small compressor is integrated inside the machine frame.

The laminating unit is equipped with an adjustable twin decurl unit:

- With a decurl blade for offset printed sheets decurling
- With a decurl roller for digital printed sheets decurling (to prevent scratches on sheets printed on both sides by digital print with sensitive inks).

## FEEDING

The FOLIANT Gemini C 400 is a manual machine. The feeding is manual. The laminating unit equipped with a synchronized feeding conveyor and an adjustable side guider for an easy loading.

## SEPARATION

The FOLIANT Gemini C 400 is a manual machine. The separation is manual. Due to the perforation of film (done in the process of laminating) the whole process is easy.

## AUTOMATIC SEPARATION

Any time later the machine can be upgraded with an automatic separator. The belt separator (sheeter) is equipped with a separating roller and a deflection wheel. The separated sheets are delivered into a reception unit or a vibrating jogger (options). More information is available at FOLIANT Gemini C 400S.

## LAMINATING FILMS

The machine laminates the BOPP films (23 – 42 microns) and Nylon films (max. 35 microns).

## OPTIONS

### FILM SUPPLY ROLL SHAFT (OPTIONAL)

Extra Film Supply Roll Shaft for quicker film replacement.



Extra Film Supply Roll Shaft

### NON-STICKY PRESSURE ROLLER (OPTIONAL)

Standard rubber pressure roller is replaced by roller with non-sticky surface. Melted glue from film cannot stick to it even under heavy pressure. Cleaning of this roller is not necessary at all. Allows laminating sheets with windows.

#### Foliant Gemini C 400

<b>Max Speed</b>	15 m / min	<b>Max. Performance</b>	1800 B3 / h
<b>Feeding</b>	Manual	<b>Temperature Control</b>	80 - 140°C
<b>Separation</b>	Manual	<b>Warming up Time</b>	5 min
<b>Paper Weight</b>	115 - 350 gsm	<b>Power Supply</b>	230 V AC, 50-60 Hz
<b>Main rollers pressure</b>	Pneumatic	<b>Power</b>	2600 W
<b>Integrated compressor</b>	Included	<b>Floor space (w x l)</b>	74 x 117 cm
<b>Min. Sheets Size (w x l)</b>	30 x 25 cm	<b>Weight</b>	152 kg
<b>Max. Sheets size (w x l)</b>	38 x 70 cm	<b>Non-sticky pressure roller</b>	Optional